

SUN SCREEN FABRIC PT-8100

APPLICATION: Curtain

TECHNICAL SPECIFICATIONS:

Weight	500g/m2	DIN EN ISO 3759, ASTM-D751
Width	3M/118"	DIN EN ISO 3759, ASTM-D751-2006
Material	PVC	DIN600001, ASTM-D7641
Base Fabric	/	DIN EN ISO 2060, ASTM-D1907
FR	B1,NFPA-701	DIN 4102-B1, NFPA 701 TEST-1
Weave Method	/	
Fixation Temperature	190-210°C, 1-2 min	
Yellowing Temperature	≥210°C	

PRINTING RESULTS:

(P=PERFECT / D=DEPENDS / NR=NOT RECOMMEND)

UV	DyeSub-Direct	DyeSub-Paper	Latex	Eco-Solvent
P	NR	NR	P	NR

STORAGE INSTRUCTIONS:

Recommended temperature and humidity: 15°C [59°F] ~ 35°C [95°F], 20 ~ 65% RH; In Original Package Shelf life 1 year.

NOTE: The numbers above are purely guidelines and may differ depending on your personal printing needs and expectations. Since the printing results depend on numerous factors, we strongly advise to test your output in order to find out if any adjustments are necessary. A legally binding assurance of certain properties of the fabric can not be derived from the information above.