

SILVER BACK FABRIC PT-8002

APPLICATION: Curtain

TECHNICAL SPECIFICATIONS:

Weight	240g/m2	DIN EN ISO 3759, ASTM-D751
Width	3.2M/126"	DIN EN ISO 3759, ASTM-D751-2006
Material	100% Polyester + PA coating	DIN600001, ASTM-D7641
Base Fabric	40*4040 Denier	DIN EN ISO 2060, ASTM-D1907
FR	B1,NFPA-701,M1	DIN 4102-B1, NFPA 701 TEST-1
Weave Method		/
Fixation Temperature		/
Yellowing Temperature		/

PRINTING RESULTS:

(P=PERFECT / D=DEPENDS / NR=NOT RECOMMEND)

UV	DyeSub-Direct	DyeSub-Paper	Latex	Eco-Solvent
D	P	P	D	NR

STORAGE INSTRUCTIONS:

Recommended temperature and humidity: 15°C [59°F] ~ 35°C [95°F], 20 ~ 65% RH; In Original Package Shelf life 1 year.

NOTE: The numbers above are purely guidelines and may differ depending on your personal printing needs and expectations. Since the printing results depend on numerous factors, we strongly advise to test your output in order to find out if any adjustments are necessary. A legally binding assurance of certain properties of the fabric can not be derived from the information above.