

NON PVC GREY BACK ROLL UP FABRIC PT-5101

APPLICATION: Blockout

TECHNICAL SPECIFICATIONS:

Weight	280g/m2	DIN EN ISO 3759, ASTM-D751
Width	3.2M/126"	DIN EN ISO 3759, ASTM-D751-2006
Material	Polyester + PA	DIN600001, ASTM-D7641
Base Fabric	300*300 Denier	DIN EN ISO 2060, ASTM-D1907
FR	B1,NFPA-701,M1	DIN 4102-B1, NFPA 701 TEST-1
Weave Method	Woven	
Fixation Temperature	190-210°C, 1-2 min	
Yellowing Temperature	≥210°C	

PRINTING RESULTS:

(P=PERFECT / D=DEPENDS / NR=NOT RECOMMEND)

UV	DyeSub-Direct	DyeSub-Paper	Latex	Eco-Solvent
P	NR	NR	P	P

STORAGE INSTRUCTIONS:

Recommended temperature and humidity: 15°C [59°F] ~ 35°C [95°F], 20 ~ 65% RH; In Original Package Shelf life 1 year.

NOTE: The numbers above are purely guidelines and may differ depending on your personal printing needs and expectations. Since the printing results depend on numerous factors, we strongly advise to test your output in order to find out if any adjustments are necessary. A legally binding assurance of certain properties of the fabric can not be derived from the information above.