

FABRIC TEXTURE NON-WOVEN WP EWP-0006

APPLICATION: Wall Decoration, Interior Decoration

TECHNICAL SPECIFICATIONS:

Material	Paper	DIN600001, ASTM-D7641	
Weight	180G+/-10G	ASTM D7641	
Width	1.27M/50"	ASTM D751-2006	
Surface	Matte		
Attainable FR	B1, ASTM-E84		
Environmental	FSC		
Glue	/		
Display Permanence (Indoor home or office)	Over 10+ years, away from direct sun.		
Display Permanence (Commercial in-window)	Over 2+ years		

PRINTING RESULTS:

(P=PERFECT / D=DEPENDS / NR=NOT RECOMMEND)

UV	DyeSub-Direct	DyeSub-Paper	Latex	Eco-Solvent
Р	NR	NR	Р	Р

STORAGE INSTRUCTIONS:

Recommended temperature and humidity: 15°C [59°F] ~ 35°C [95°F], 20 ~ 65% RH; In Original Package Shelf life 1 year. NOTE: The numbers above are purely guidelines and may differ depending on your personal printing needs and expectations. Since the printing results depend on numerous factors, we strongly advise to test your output in order to find out if any adjustments are necessary. A legally binding assurance of certain properties of the fabric can not be derived from the information above.