

## COREOPSIS WV EWV-0025

**APPLICATION:** application\_value

### TECHNICAL SPECIFICATIONS:

Material	Polyester+Vinyl	DIN600001, ASTM-D7641
Weight	465G	ASTM D7641
Width	1.37M/54"	ASTM D751-2006
Surface	Matte	
Attainable FR	B1/ASTM-E84	
Environmental	Reach	
Water Resistance	Available	
Display Permanence (Indoor home or office)	Over 10+ years, away from direct sun.	
Display Permanence (Commercial in-window)	Over 2+ years	

### PRINTING RESULTS:

( P=PERFECT / D=DEPENDS / NR=NOT RECOMMEND )

UV	DyeSub-Direct	DyeSub-Paper	Latex	Eco-Solvent
P	NR	NR	P	P

### STORAGE INSTRUCTIONS:

Recommended temperature and humidity: 15°C [59°F] ~ 35°C [95°F], 20 ~ 65% RH; In Original Package Shelf life 1 year.

NOTE: The numbers above are purely guidelines and may differ depending on your personal printing needs and expectations. Since the printing results depend on numerous factors, we strongly advise to test your output in order to find out if any adjustments are necessary. A legally binding assurance of certain properties of the fabric can not be derived from the information above.